

AKSİYEL FANLI SU SOĞUTMA KULELERİ AXIAL FAN WATER COOLING TOWERS

MODEL	Soğutma Kapasitesi (Cooling Capacity) Kcal/h	DEBİ (m³/h) (Flow m³/h)		KULE AĞIRLIĞI (Tower Weight)		FAN VERİLERİ (Fan Data)		MOTOR 380V,50Hz (Engine 380V,50Hz)	POMPA BAS Yük.mm ss
		Min	Max	Boş	Dolu	Çap (mm)	Devir (d/d)		
06 AFK 13	25.000	2,7	4,5	115 kg	222 kg	450	1410	0,37 Kw	1100
06 AFK 15	35.000	4	6,6	115 kg	244 kg	450	1410	0,37 Kw	1450
06 AFK 17	40.000	5	8,1	130 kg	303 kg	550	1395	0,75 Kw	1550
06 AFK 21	90.000	9,5	18,1	298 kg	537 kg	750	820	1,1 Kw	1700
06 AFK 23	120.000	12,5	23,4	345 kg	719 kg	900	625	1,1 Kw	1735
06 AFK 25	150.000	15,9	29,7	347 kg	721 kg	900	785	2,2 Kw	1780
06 AFK 27	200.000	20,6	39,3	413 kg	807 kg	900	785	2,2 Kw	2470
06 AFK 29	225.000	23,6	45	485 kg	907 kg	900	785	2,2 Kw	2620
06 AFK 33	385.000	37,9	76,5	603 kg	1183 kg	1200	645	4 Kw	2500
06 AFK 35	455.000	45,4	90,9	836 kg	1753 kg	1200	660	5,5 Kw	2620
06 AFK 37	595.000	59,5	119	1160 kg	2488 kg	1200	635	5,5 Kw	2780
06 AFK 33x2 (İKİZ)	760.000	76	152	1176 kg	2336 kg	1200x2	645	5,5 Kw x 2	3000
06 AFK 35x2 (İKİZ)	1.000.000	100	200	1642 kg	3476 kg	1200x2	660	5,5 Kw x 2	3144
06 AFK 37x2 (İKİZ)	1.200.000	120	240	2290 kg	4946 kg	1200x2	635	5,5 Kw x 2	3336
06 AFK 37x3 (ÜÇÜZ)	1.800.000	180	360	3420 kg	7404 kg	1200x3	635	5,5 Kw x 3	3614

06 AFK 13 - 06 AFK 37 EBATLARI VE GİRİŞ ÇIKIŞ ÖLÇÜLERİ SIZES 06 AFK 17 - 06 AFK 37 AND INPUT AND OUTPUT DIMENSIONS

MODEL	KAPASİTE Kcal/h (AT 5 C) (Capacity)	A	B	C	D	E	F	G	H	I	J	K	L	SU GİRİŞ VE ÇIKIŞ (Water Inlet And Outlet)		TAHLİYE MAŞONU (Evacuation Outlet)	FLATÖR
														FLANŞ	MANŞON		
06 AFK 13	25.000	965	950	470	530	-	810	580	260	615	-	1030	-	-	1 ½"	1 ½"	½"
06 AFK 15	33.000	965	1210	470	530	-	1070	710	260	615	-	1290	-	-	1 ½"	1 ½"	½"
06 AFK 17	40.000	1135	1210	570	630	-	1070	710	340	715	-	1290	-	-	2"	1 ½"	½"
06 AFK 21	90.000	1365	1570	790	870	330	1260	865	340	1050	140	1900	370	-	2 ½"	1 ½"	½"
06 AFK 23	120.000	1465	1570	940	1020	330	1260	865	340	1265	140	1900	370	-	2 ½"	1 ½"	½"
06 AFK 25	150.000	1465	1640	940	1020	360	1260	865	340	1265	140	2000	410	-	2 ½"	1 ½"	½"
06 AFK 27	200.000	1465	2100	940	1020	360	1800	1265	340	1265	140	2560	410	4"	-	1 ½"	½"
06 AFK 29	225.000	1710	1980	940	1020	360	1670	1140	340	1265	140	2430	410	4"	-	1 ½"	½"
06 AFK 33	385.000	1710	1980	1240	1320	360	1670	1140	340	1565	165	2430	410	4"	-	2"	½"
06 AFK 35	455.000	2000	1980	1240	1320	430	1650	1140	340	2001	165	2410	460	4"	-	2"	½"
06 AFK 37	595.000	2200	1980	1240	1320	430	1650	1140	340	2500	170	2410	460	4"	-	2"	½"
06 AFK 33x2 (İKİZ)	760.000	1710	1980	1240	1320	360	1670	1140	340	2820	165	2430	460	6"	-	2"	½"
06 AFK 35x2 (İKİZ)	1.000.000	2000	1980	1240	1320	360	1670	1140	340	3900	165	2410	460	6"	-	2 ½"	½"
06 AFK 37x2 (İKİZ)	1.200.000	2200	1980	1240	1320	360	1670	1140	340	4900	170	2410	460	8"	-	2 ½"	½"
06 AFK 37x3 (ÜÇÜZ)	1.800.000	2200	1980	1240	1320	360	1670	1140	340	7300	170	2410	460	8"	-	2 ½"	½"

